

# PRODUCT DATA SHEET

# ALL WALL MATT

## 10 YEAR WARRANTY

### GENERAL DESCRIPTION

All Wall Matt is a superior waterbased quality acrylic emulsion paint.

### APPLICATION AREAS

- Interior & Exterior Use
- New Walls & Ceilings
- Cement Plaster
- Concrete
- Porous Brickwork
- Various types of building boards
- Ceramic Brickwork

### PRODUCT FEATURES

- Waterbased
- Easy Application
- Waterproof
- UV Resistant

### PRODUCT DATA

<b>Physical Form:</b>	Modified Acrylic Emulsion.
<b>Finish:</b>	Smooth matt finish.
<b>Practical:</b>	4-6m <sup>2</sup> per liter depending on surface porosity, colour and application method.
<b>Properties:</b>	Touch dry in 30 minutes. Over-coating 1h depending on ambient temperature and vapour pressure.
<b>Flashpoint:</b>	Waterbased.
<b>Equipment Cleaning:</b>	Water. Do not allow the paint to get dry on the equipment.
<b>Solids:</b>	Range 40% - 51%
<b>DFT:</b>	80µ 1 coat - recommended 160µ 2 coats

### APPLICATION DETAILS

<b>Mixing:</b>	Always stir well before use with a flat paddle.
<b>Application Method:</b>	Brush, roller or airless spray gun.
<b>Thinning:</b>	Not more than 5-10% water.
<b>Cleaning:</b>	Clean up with water. Do not allow product to dry on equipment.
<b>Application:</b>	<p><b><u>For Brush or Roller Application:</u></b></p> <ul style="list-style-type: none"><li>• Apply 2 coats of All Wall Matt - to achieve proper penetration and allow to dry for 1 hour between coats and an additional 2 hours between in cold wet weather.</li><li>• Porous surfaces may require a third coat to ensure surface is properly coated</li></ul> <p><b><u>For Airless Spray Application:</u></b></p> <ul style="list-style-type: none"><li>• Dilute the primer with no more than 10% by volume with water.</li><li>• Apply 2 coats of All Wall Matt - to achieve proper penetration and allow to dry for 1 hour between coats and an additional 2 hours between in cold wet weather.</li><li>• Porous surfaces may require a third coat to ensure surface is properly coated</li></ul>

### SURFACE PREPARATION

<b>All Surfaces:</b>	<ul style="list-style-type: none"><li>• Remove dust, foreign material, fungal and algae growth with Degreaser or Sugar Soap.</li><li>• For Oil stains, use Heavy Duty Degreaser and scrub down with a broom or hard brush.</li><li>• Wash off thoroughly with water.</li><li>• All surfaces have to be sound and dry before painting.</li><li>• If the surface of the concrete is powdery or weak, apply Bonding Liquid (Solvent Base) first coat.</li></ul>
----------------------	--

### SECONDARY PRODUCTS YOU MAY NEED

- Brushes, rollers and paint trays
- Hard brush, broom or wire brush
- Degreaser or Sugar Soap
- Heavy Duty Degreaser
- Dropsheets

### HEALTH & SAFETY

This product is non flammable. Avoid contact with eyes and mouth. If bodily contact is made, rinse off immediately with water. Do not ingest, if ingested, do not induce vomiting, seek medical attention.

#### DISCLAIMER ADVICE:

*The information given in this product information sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristics is given or implied. Mocnort Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Mocnort Paints products. Mocnort Paints reserves the right to update product specifications without prior notice.*