

PRODUCT DATA SHEET

UNICOAT

10 YEAR WARRANTY

GENERAL DESCRIPTION

Unicoat is a superior quality, alkali resistant, UV resistant water based acrylic coating with exceptional adhesion and durability.

APPLICATION AREAS

- Interior and exterior surfaces
- For new galvanized and cement surfaces

PRODUCT FEATURES

- Unicoat is a weather, alkali resistant and UV resistant acrylic coating
- Available in deep and pastel bases
- Suitable for new galvanised and cement surfaces
- Excellent adhesion
- Easy no-mess application properties
- Quick drying - 2 coats can be applied in one day
- High Sheen

PRODUCT DATA

Physical Form:	Waterbased Emulsion type (Pure Acrylic. Non Toxic)
Finish:	High Sheen
Practical:	± 8m ² per liter depending on surface porosity and application method
Properties:	Touch dry in 1hour. Over-coating in 2 hours depending on ambient temperature, vapour pressure and humidity
Flashpoint:	Waterbased
DFT - 2Coat:	65µ per coat - recommended 130µ

APPLICATION DETAILS

Mixing:	Always stir well with a flat paddle before use.
Application Method:	Brush or Roller or Airless Spray Gun
Thinning:	Not more than 5-10% water
Cleaning:	Water. Do not allow paint to dry on the equipment
Application:	<p><u>For Brush or Roller Application:</u></p> <ul style="list-style-type: none">• Apply 1 coat of paint to achieve proper penetration and allow to dry for 2-4hours, and an additional 6 hours in cold wet weather.• Apply a second coat to ensure the substrate is properly coated. <hr/> <p><u>For Airless Spray Gun Application:</u></p> <ul style="list-style-type: none">• Dilute the paint with no more than 10% by volume with water.• Apply one coat of paint to achieve proper penetration and allow to dry for 2-4hours, and an additional 6 hours in cold wet weather.• Apply a second coat to ensure the substrate is properly coated.

SURFACE PREPARATION

Walls Newly Plastered	<ul style="list-style-type: none">• Remove dust, foreign material, fungal and algae growth.• If friable or powder, seal with primer• Apply 1 coat of suitable primer• Fill all visible cracks and spot prime if required• Apply 2 coats of Shield to ensure total coverage of porous surfaces• Moisture content of the new plaster must be less than 10%
Previously Painted Surfaces	<ul style="list-style-type: none">• Make sure old paint coatings are firm and solid.• Remove all loose, flaking and bubbling paint with paint stripper.• Remove all dust, grease, foreign material, fungal and algae growth• Rinse all detergents and products thoroughly with water and allow to dry• Apply 1 coat of suitable primer• Fill all visible cracks and spot prime if required• Apply 2 coats of Shield to ensure total coverage

SECONDARY PRODUCTS YOU MAY NEED

- Drop Sheets
- Brushes, rollers and paint trays
- Bonding liquid

- Power crack filler
- Paint stripper

HEALTH & SAFETY

This product is non-flammable. Avoid contact with eyes and mouth. If bodily contact is made, rinse immediately with water. Do not ingest, if ingested, do not induce vomiting, seek medical attention.

DISCLAIMER ADVICE:

The information given in this product information sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristics is given or implied. Mocnort Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Mocnort products. Mocnort Paints reserves the right to update product specifications without prior notice.



MOCNORT



PAINTS

...Colouring lives one brush stroke at a time...