

PRODUCT DATA SHEET

WALL & CEILING

5 YEAR WARRANTY

GENERAL DESCRIPTION

Wall & Ceiling is a superior waterbased quality acrylic emulsion paint.

APPLICATION AREAS

- New Walls & Ceilings
- Cement Plaster
- Concrete
- Porous Brickwork
- Various types of building boards
- May also be applied to suitably primed wood, fibre-cement and gypsum plaster.

PRODUCT FEATURES

- Long life durability
- Excellent alkali resistance
- Waterbased
- Semi washable

PRODUCT DATA

Physical Form:	Modified Acrylic Emulsion.
Finish:	Smooth matt finish.
Practical:	4-6m ² per liter depending on surface porosity, colour and application method.
Properties:	Touch dry in 30 minutes. Over-coating 1 hour depending on ambient temperature and vapour pressure.
Flashpoint:	Waterbased
Solids:	Range 40% - 51%

APPLICATION DETAILS

Mixing:	Always stir well before use with a flat paddle.
Application Method:	Brush, roller or airless spray gun.
Thinning:	With water – not more than 5-10% water.
Cleaning:	Clean up with water. Do not allow product to dry on equipment.
Application:	<p><u>For Brush or Roller Application:</u></p> <ul style="list-style-type: none">• Apply one coat of Wall & Ceiling to achieve proper penetration, allow to dry for 4 - 6 hours and an additional 6 hours in cold wet weather.• Porous surfaces may require a second coat to ensure surface is properly coated so that the surface does not show through the primer. <hr/> <p><u>For Airless Spray Application:</u></p> <ul style="list-style-type: none">• Dilute the primer with no more than 10% by volume with water.• Apply one coat of Wall & Ceiling to achieve proper penetration and allow to dry for 4 - 6 hours, and an additional 6 hours in cold wet weather.• Porous surfaces may require a second coat to ensure surface is properly coated so that the surface does not show through the primer.

SURFACE PREPARATION

All Surfaces:

- Ensure that all surfaces are thoroughly clean, sound dry and free from any contaminants such as dirt, salt algae, oil, grease or loose flaking paint.
- New surfaces must be clean and dry, loose and brittle material must be brushed or sanded off, washed with clean water and left to dry. Moisture content of the new plaster must be less than 10%.
- Previously painted surfaces must be clean and dry. Loose and brittle material such as chalk must be brushed or sanded off, washed with clean water and left to dry.

SECONDARY PRODUCTS YOU MAY NEED

- Dropsheets
- Brushes, rollers and paint trays
- Wall Plaster
- Degreaser
- Qualisheen / QualiCote

HEALTH & SAFETY

This product is non flammable. Avoid contact with eyes and mouth. If bodily contact is made, rinse off immediately with water. Do not ingest, if ingested, do not induce vomiting, seek medical attention.

DISCLAIMER ADVICE:

The information given in this product information sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristics is given or implied. Mocnort Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Mocnort Paints products. Mocnort Paints reserves the right to update product specifications without prior notice.